



BRAMC 5-in-1 Air Quality Monitor PM2.5 PM10 Formaldehyde CO2 VOCs



SKU: BRSMART128SE
Manufacture warranty period: 12 months

Product overview:

BR-SMART-128s portable handheld 5-in-1 air quality monitor is a real-time air quality monitoring instrument used to detect PM2.5, PM10, carbon dioxide (CO₂), formaldehyde (HCHO) concentration and VOCs in the indoor and outdoor environment. This product uses high-precision sensor chip and operation, will convert PM2.5, PM10, CO₂, formaldehyde and VOCs concentration in the air into visual data, to monitor the air quality, provide effective protection for family health.

Scope of application:

Any indoor or outdoor environment, such as inside the house, office environment, vehicles or outdoor shelter.





Product specifications:

- Display mode: 2.4" TFT colour screen
- **PM2.5 and PM10** using light scattering measurement method
 - Measuring range: 0 to 999 $\mu\text{g}/\text{m}^3$
 - Resolution: 1 $\mu\text{g}/\text{m}^3$
 - Accuracy: $\pm 10\%$
- **Formaldehyde (HCHO)** using electrochemical sensor measurement method
 - Measuring range: 0 to 3.000 mg/m^3
 - Resolution: 0.001 mg/m^3
 - Accuracy: $\pm 10\%$
- **Carbon Dioxide (CO2)**
 - Measuring range: 0 to 5000ppm
 - Resolution: 1ppm
 - Accuracy: $\pm 10\%$
- **VOCs** using semiconductor sensor test
 - Measuring range: 0 to 9.999 $\mu\text{g}/\text{m}^3$
 - Resolution: 0.001 mg/m^3
 - Accuracy: $\pm 10\%$
- Battery power indicator
- Storage: 10,000 records
- Data record interval at every 1 minute
- Data record measure duration:
 - Continuous Mode
 - 10 mins mode
 - 15 mins mode
 - 20 mins mode
- Built-in Rechargeable Battery (2200AH)
- Power adapter:
 - Input voltage: AC220V, 50/60Hz, 0.45A
 - Rated output voltage: DC5 V
 - Rated output current: 500mA

Environment for use:

- Temperature range: 0 to 50 °C
- Humidity range: 0 to 90%RH
- Pressure: 1 standard pressure

Product Dimension:

- Dimensions: 65 x 140 x 40mm
- Weight: 220g

Package included:

- Air quality monitoring unit
- 1x 128MB Micro SD Card
- Power adapter (EU plug)
- Data/Charging cable
- User Guide





6 channel particle precision laser sensor

6 channel fine particle number measurement PM0.3 PM0.5 PM1.0 PM2.5 PM5.0 PM10
 3-channel particulate matter mass measurement PM1.0 PM2.5 PM10



Built-in TF memory card

Record complete changes in pollution data

Large amounts of data can be imported into computers



Data in Excel format.

A	B	C	D	E
Date & Time	PM2.5 (µg/m3)	CO2 (ppm)	Formaldehyde (mg/m3)	VOCs (mg/m3)
18/10/2018 04:13 PM	11	0	0	0
18/10/2018 04:14 PM	10	0	0	0
18/10/2018 04:15 PM	10	1315	0	1.546
18/10/2018 04:16 PM	11	1250	0	1.424
18/10/2018 04:17 PM	11	1131	0	1.298
18/10/2018 04:18 PM	11	1110	0	1.277

Decoration hazard alarm ((🔔))

Hazard alarm do not guess, icon + frequency conversion buzzer hazard rating

Alarm threshold

HCHO mg/m³ <0.10 0.10 < data < 0.30 >0.30

CO2 ppm <1000 1000 < data < 2000 >2000

TVOC mg/m³ <0.60 0.60 < data < 1.00 >1.00

PM2.5 µg/m³ <35 35 < data < 150 >150

livable Window ventilation Should not stay Leave soon