

HM Digital - COM-100 (Upgraded Model)



SKU: COM-100 Bar Code: 891144000007 Manufacture warranty period: 12 months The COM-100 is a professional grade level EC/TDS/Temp meter ideal for all water quality testing, hydroponics, water purification applications, wastewater regulation, aquaculture, colloidal silver, labs & scientific testing, pools & spas, ecology testing, boilers & cooling towers, water treatment and more.

Features:

- Measures electrical conductivity (EC), total • dissolved solids (TDS), salinity and temperature.
- **UPGRADED:** Four scales: µS, mS, **ppm 0.5 (NaCl)** Scale & 0.7 (442[™]) Scale
- Automatic Temperature Compensation (ATC) using three temperature coefficients
- Waterproof housing (IP-67 rating) ٠
- Digital Calibration (push button) to any point within the meter's range
- Auto-off function, data-hold function and low-battery • indicator
- Display: large and easy-to-read LCD screen ٠ includes simultaneous temperature reading.
- Replaceable Sensor (model SP-C1)
- Factory Calibrated: The COM-100 meter is calibrated with a 1413 µS solution.
- UPGRADED: Includes translucent cap, 2 x AAA • batteries and lanyard.

Applications:

- Aquaculture
- Aquarium
- Drinking Water
- Food & Beverage
- Hydroponics
- Industrial
- Pool/Spa
- Water Treatment

Specifications:

- EC Range: 0 9990 µS; 0 9.99 mS
- TDS Range: 0 8560 ppm (0.7 Scale); 0 8.56 ppt (0.7 Scale)
- 0 5000 ppm (0.5 Scale); 0-5.00 ppt (0.5 Scale)
- Temperature Range: 0-55 °C; 32-130°F
- Resolution: 0-99: 0.1 μS/ppm/ 0.01mS/ppt; 100-999: 1 μS/ppm; 1000-9990: 10 μS/ppm. Temp. resolution is 0.1 °C/F
- Accuracy: +/- 2%
- EC to TDS Conversion Factor: Non-linear conversions for KCI, 442TM or NaCl solutions, selected by the user.
- Probe: Detachable platinum electrodes
- Housing: IP-67 Waterproof (submersible; floats)
- UPGRADED: Power source: 2 x AAA
- Dimensions: 18.5 x 3.4 x 3.4 cm (7.3 x 1.3 x 1.3 inches)
- Weight: 127g (4.5 oz)
- 442 is a registered trademark of the Myron L Company.

Standards Certification:

• CE

Package Includes:

- HM COM100 meter
- User's Guide
- Lanyard
- 2 x AAA batteries

